

Mobile bunkerskid including feeding conveyor

TYPE

Specifications

Machine

Type Mobile bunker skid
Power
Year 2019
Hours 0
Condition As good as new

Highlights

Additional information

Bunker Type BRB 1200 * 5000

Belt width	- 1200 mm.
Belt length	- 5000 mm (shaft distance)
Drive power	- 7,1 kW
Belt speed	- 1 - 4 meter/minute
	- The motor is equipped with a frequency inverter
for adjusting the belt speed	
Ingress Protection	- IP-65.
Material rubber belt	- Type EP500/3, 6+2 Total thickness 8,8mm. Wear resistant.

Incline Belt Type TBM 1200 * 8500

Belt width	- 1200 mm.
Belt length	- 8500 mm (shaft distance)
Drive power	- 3 kW
Belt speed	- 40 meter/minute
Ingress Protection	- IP-65.
Material rubber belt	- Type 400/3, 4+2, in 3 layers with a top and bottom layer, total thickness 8.8 mm, wear-resistant. Fitted with cleats (material is fed up well, there is a risk of contamination)

Semi-Mobile rugged skid

Height: 2560 mm.
Width: 2430 mm.
Length: 9960 mm.

Switchbox

Switchbox for bunker belt and incline belt



















